

AEC Community

ANACONDA SEALTITE® CONDUIT SYSTEMS

Our electrical conduit and fittings protect wiring and cable from

- Stress and strain
- Extreme temperatures
- Water and corrosion

**TO
CONNECT
AND
PROTECT**

Find us in

MasterSpec®

Powered by Deltek Specpoint®

ANAMETELECTRICAL.COM

SALES@ANAMETELECTRICAL.COM

PHONE: (800) 230-3718

ANAMET Electrical, Inc. 

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

- Easy to Work With
- Web Access to Specs
- Copy and Paste
- UL Listed Conduit

Connect and Protect

UA

3/8 to 4 inch diameter

UL listed and CSA approved flexible conduit

SPECIFICATIONS

- Uses standard liquid tight connectors
- Color: Pantone Matching System colors
- UL and CSA approved
- UL certified for temperature ranges -40°F to +176°F (-40°C to +80°C).
CSA certified for 60°C dry / 60°C oil.

APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"

ZHUA

3/8 to 2 inch diameter

Zero Halogen/Low Smoke Flexible Conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant
- UL Approved to UL-94 V-0 and UL-360. # E18917
- Meets or exceeds: ASTM-E162 (Flame spread); ASTM-E662 (Smoke density); Bombardier SMP-800C (Toxic gas generation)
- CSA File No. LL15275

APPLICATIONS

- Commercial applications where Zero Halogen and Low Smoke conduit is specified
- Rail and aerospace transport
- Commercial buildings

Code-compliant ANACONDA SEALTITE® conduit and fittings

CW-BLUE

1/2 to 3 inch diameter

Computer flexible conduit

SPECIFICATIONS

- Uses standard liquid tight connectors
- Color: Blue
- Temp. range: -40°F to +176°F (-40°C to +80°C)

APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"
- Approved for use in cable raceways and under raised floors (NEC Article 645.5 (E)(2))

HTUA - HEAVY DUTY

3/8 to 4 inch diameter

UL/CSA High Temperature Flexible Conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Temp. range: -51°F to + 221°F (-46°C to +105°C) CSA max +167°F (+75°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are required
- Steel and petrochemicals industries

Stainless Steel Fittings

ANACONDA SEALTITE® fittings and conduit join securely to protect equipment from contamination, intrusion, strain, extreme temperatures and corrosion.



RoHS WEEE Compliant

1-800-230-3718 cs@anametelectrical.com www.anametelectrical.com

ANAMET Electrical, Inc. 