

Airport Construction


ANACONDA SEALTITE® CONDUIT

ANAMET Electrical conduit and fittings protect wiring from

- Intrusion and security breach
- Stress and strain
- Extreme temperatures
- Water and corrosion

**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM

ANAMET Electrical, Inc. 

ANAMET Electrical, Inc. is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

Connect and Protect

ANACONDA SEALTITE® liquid tight conduit and fittings

ZHUA 3/8 to 4 inch diameter

Zero Halogen, Low smoke, UL Listed flexible conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- UL Approved to UL-94 V-0 and UL-360. DXHR.E18917
- Meets or exceeds: ASTM-E162 (Flame spread); ASTM-E662 (Smoke density); Bombardier SMP-800C (Toxic gas generation)
- CSA File No. LL15275

APPLICATIONS

Safety applications where low smoke and zero halogen are required

XTHF 1/2 to 1 inch diameter

Zero Halogen, Low smoke flexible conduit

SPECIFICATIONS

- Liquid tight Flexible Metal Conduit
- Rated for temperature range of -94°F to +392°F (-70°C to +200°C) and incursions up to 500°F (260°C)
- Can be used in applications that do not require approvals
- Durable, sunlight resistant, flame retardant, low smoke and zero halogen silicone jacket that resists heat, oil and corrosive chemical breakdown.
- Flexible metal core meets "Construction" requirements of UL Std. 360 sizes 1/2" through 1"

MEETS CHEMICAL COMPATIBILITY (MIL STD 810F, 504)

- Fuel - Jet Propellant 8
- Hydraulic fluid - Royco 756
- Lube oil - Royco 500
- Cleaner - Calla 855
- Solvent (Isopropyl Alcohol) - TT-I-735
- De-Icer - E36 Runway De-Icer
- Coolant - Coolanol 25R
- Fire Extinguisher foam - Amerex AFFF

MEETS or EXCEEDS the following STANDARDS

- Flame Resistant IEC 60614-1
- Halogen Free IEC 60614-1
- Toxicity Index NES 713 (1.0)
- Low Smoke Index NES 711
- Solar Weathering IEC 60068-2-5
- Oxygen Index 29.2

APPLICATIONS

- Designed for the most extreme temperature applications
- Silicone jacket has superior resistance to chemical breakdown

CW-BLUE

1/2 to 3 inch diameter
UL listed and CSA approved
flexible conduit

SPECIFICATIONS

- Uses standard liquid tight connectors
- Color: Blue
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UL and CSA approved, UL-360. DXHR.E18917, CSA File No. LL15275

APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"
- Approved for use in cable raceways and under raised floors (NEC Article 645.5 (E)(2))
- NEC 300.22 (D) Information Technology Equipment

UA 3/8 to 4 inch diameter

UL listed and CSA approved
flexible conduit

SPECIFICATIONS

- Uses standard liquid tight connectors
- Color: Pantone Matching System colors
- UL and CSA approved, UL-360. DXHR.E18917, CSA File No. LL15275
- UL certified for temperature ranges -40°F to +176°F (-40°C to +80°C). CSA certified for 60°C dry / 60°C oil

APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"



RoHS WEEE
Compliant