

# Animal, Plant or Fishery Facilities

## ANACONDA SEALTITE® CONDUIT

Flexible, armored protection,  
anti-microbial and easy to clean,  
electrical conduit and fittings  
protect wiring from

- Soap and Detergent
- Contamination
- Stress and strain
- Water and corrosion

**TO  
CONNECT  
AND  
PROTECT**

NSF

PHONE: (800) 230-3718  
ANAMETELECTRICAL.COM  
SALES@ANAMETELECTRICAL.COM

**ANAMET Electrical, Inc.** 

ANAMET Electrical is the exclusive manufacturer of  
ANACONDA SEALTITE® liquid tight wiring conduit and  
industrial stripwound hose.

# Deliver electricity safely

## ANACONDA SEALTITE® Food Grade liquid tight conduit and stainless steel fittings

Food Grade conduit and fittings certified for hygienic environments



### FGUA

- 3/8 to 2 inches diameter
- Galvanized steel core with thick, smooth, PVC cover
- Color: White, clear or colors
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UL Approved #E18917

### FGSS

- 3/8 to 2 inches diameter
- 316 Stainless steel core with thick, smooth, PVC cover
- Color: Clear, white or colors
- Temperature range: -40°F to +176°F dry / 140°F wet / 158°F oil with brief incursions to +221°F (-40°C to +80°C dry / 60 °C wet / 70°C oil with brief incursions to +105°C)

### FG

- 3/8 to 2 inches diameter
- Galvanized steel core with thick, smooth, PVC cover
- Color: White, clear or colors
- Temperature range: -40°F to +176°F dry / 140°F wet / 158°F oil with brief incursions to +221°F (-40°C to +80°C dry / 60 °C wet / 70°C oil with brief incursions to +105°C)

### CNP

- 3/8 to 2 inches diameter
- Smooth inner wall PVC core covered with a nylon fiber braid bonded to a smooth, oil resistant, PVC cover
- Color: Orange or gray
- Temperature range: -4°F to +140°F (-20°C to +60°C)
- UL 1660 Approved DX00.E75863
- CSA Approved #LL15275-10

### Nickel-Plated Brass Fittings

- 3/8 to 2 inches diameter
- Nickel-Plated Brass with a TPE clamping ring
- Temp. range: -49°F to +221°F (-45°C to +105°C)
- cULus 514B Approved DWTT.E234207
- Type A Non-Metallic flexible conduit
- Compact design ideal for tight spaces
- High-end appearance for good presentation



RoHS WEEE Compliant