

Prolonged UV Exposure Conduit

ANACONDA SEALTITE® CONDUIT

ANAMET conduit and fittings
protect wiring and cable from

- Prolonged solar exposure
- Prolonged UV exposure



**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM

ANAMET Electrical, Inc. 

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

ANACONDA SEALTITE® liquid tight conduit

UVUA UL LISTED UV (SUNLIGHT) RESISTANT CONDUIT, TRADE SIZES 3/8 TO 2 INCHES



DESCRIPTION

- Liquid tight flexible metal conduit
- Approved for direct burial and in concrete
- Uses standard liquid tight connectors for easy installation
- Protection of 1000 volt and lower potential circuits
- UL certified for temperature ranges -40°F to +176°F (-40°C to +80°C)
- Greatly exceeds UL 360 Sunlight Resistance requirements
- Independently proven durability, after UV exposure over 3.8 times longer than the UL 360 standard in weatherometer

COMPLIANT WITH NEC ARTICLES

- 300.22 (D) Information Technology Equipment
- 250.102, 250.118(5) and 250.134(B) Equipment Grounding
- Suitable for hazardous locations per NEC Articles
 - 501.10 (B) (2) Class I Div. 2
 - 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
 - 503.10 (A) (3) and (B) Class III Div. 1 & 2
- 350 Liquid tight Flexible Metal Conduit (LFMC)
- 645.5 (E) (2) Under raised floors

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight), corrosion and oil resistant
- UL 360 Approved DXHR.E18917, NEC Article 350, NFPA 79 (2021 Edition) Section 13.5.4 LFMC and NFPA 130 (2023 Edition) Section 8.6.7.4 LFMC

APPLICATIONS

- Where UL approval is required
- Outdoor signs, railroad crossings, ultraviolet lighting, solar panels and wind turbines
- Prolonged exposure to UV light or sunlight



RoHS WEEE Compliant