

# Wastewater Treatment

## ANACONDA SEALTITE®

ANAMET Electrical conduit and fittings protect wiring and cable from

- UV exposure
- Corrosion
- Waste Water
- Water Treatment Byproducts



**TO  
CONNECT  
AND  
PROTECT**

PHONE: (800) 230-3718  
ANAMETELECTRICAL.COM  
SALES@ANAMETELECTRICAL.COM

**ANAMET Electrical, Inc.** 

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

# Protect from exposure and wear

## ANACONDA SEALTITE® liquid tight conduit and fittings

### **EFL** 3/8 to 4 inch diameter Liquid Tight, Flexible, Metallic Conduit

#### SPECIFICATIONS

- Aluminum core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -4°F to +176°F (-20°C to +80°C)
- UV (sunlight) and corrosion resistant
- Lightweight and extra flexible

#### APPLICATIONS

Applications where no approval is required

### **HFL** 3/8 to 4 inch diameter Zero Halogen/low smoke jacket on Aluminum core

#### SPECIFICATIONS

- Aluminum core with with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- Lightweight and extra flexible

#### APPLICATIONS

Applications where no approval is required

### **HCSS** 3/8 to 2 inch diameter Extreme Temperature, Corrosion resistant

#### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) and extra corrosion resistant
- Oil resistant

#### APPLICATIONS

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required

### **HFSS** 3/8 to 2 inches Zero Halogen/low smoke 316 stainless steel

#### SPECIFICATIONS

- 316 stainless steel core with liquid tight TPE jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

#### APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Safety applications where low smoke and zero halogen are required

## STAINLESS STEEL AISI-316 FITTINGS

3/8 to 2 inches

#### SPECIFICATIONS

- AISI-316 body with AISI-304 Ferrule, a lock nut and PA6 clamping ring
- Each fitting has a sealing ring and locknut
- Color: Metallic
- Temp. range: -49°F to +221°F (-45°C to +105°C)
- cULus 514B Approved DWTT.E234207

#### APPLICATIONS

- Fitting for metallic flexible conduit
- Premium Stainless 316 for the best corrosion resistance.
- Compact design for tight spaces
- Available in 90-degree, 45-degree and straight configurations



Flexibly connect and protect wiring from UV exposure, corrosion, waste and water treatment byproducts with ANACONDA SEALTITE® conduit and fittings.



RoHS WEEE Compliant