

# FITTINGS

## SEALTITE® SERIES

ANACONDA SEALTITE® fittings and conduit are manufactured to high standards for easy installation and reliable operation. Conduit and fittings join securely to protect equipment from contamination, intrusion, strain, extreme temperatures and corrosion. Fittings are available in nickel-plated brass and 304 and 316 stainless steel to withstand harsh operating conditions.



## RECOMMENDED LFMC FITTING TIGHTENING TORQUE VALUES

TRADE SIZE	TIGHTENING TORQUE (LBF-FT)	TRADE SIZE	TIGHTENING TORQUE (LBF-FT)
3/8"	16.7	2"	133.3
1/2"	25.0	2-1/2"	133.3
3/4"	41.7	3"	133.3
1"	58.3	3-1/3"	133.3
1-1/4"	83.3	4"	133.3
1-1/2"	100.0	See UL 514B/CSA C22.2 18.3 Table 15 Tightening Torque for metric values	

SEALTITE®  
FITTINGS

## FITTING SELECTION GUIDE FOR IP RATING

FITTING SERIES	STOCK ITEM	INSULATED THROAT	CONSTRUCTION EF, EFST, UA, CW	FOOD GRADE FG, FGUA, FGSS	HARSH ENVIRONMENT HTUA, HC, HCX, HFL ZHUA, OR, FG, EFL	SHIELDTITE® AND SHIELDTITE® Z1	NMUA (NON-METALLIC) TYPE B	MTC (MACHINE TOOL CONDUIT)	CNP TYPE A
NPT Fittings LFMC Zinc-Plated Steel	Yes	Yes	IP 66/67	IP 66/67	IP 66/67	IP 66/67	No	IP 65	No
NPT / ISO Compact LFMC Nickel-Plated Brass	Yes	Yes	IP 66/67	IP 66/67	IP 66/67	IP 66/67	No	IP 65	No
NPT Compact LFMC 316 Stainless Steel	Yes	Yes	IP 66/67	IP 66/67	IP 66/67	IP 66/67	No	IP 65	No
NPT LFMC 304 Stainless Steel	Yes	Yes	IP 66/67	IP 66/67	IP 66/67	IP 66/67	No	IP 65	No
NPT Food Grade LFMC 316 Stainless Steel	Yes	No	IP 66/67	IP 68	IP 66/67	IP 66/67	No	IP 65	No
Type B NMUA Fittings LFNC Nylon 66	Yes	No	No	No	No	No	IP 66/67	No	No
Type A CNP Fittings LFNC Nickel-Plated Brass	Yes	Yes	No	No	No	No	No	No	IP 66/67

### Ingress Protection (IP ratings)

- IP 65 - Protected from total dust ingress. Protected from low pressure water jets.
- IP 66 - Protected from total dust ingress. Protected from high pressure water jets from any direction.
- IP 67 - Protected from total dust ingress. Protected from immersion to 1 meter depth.
- IP 68 - Protected from total dust ingress. Protected from immersion to 3 meters depth.
- IP 69 - Protected from total dust ingress. Protected up to 40 Bar high pressure with these fittings.

Zinc-plated fittings provide marginal corrosion resistance. Not to be used in salt or corrosive environments. Nickel-Plated Brass fittings provide better protection against corrosion. Use to prevent galvanic corrosion in neutral pH. 316 Stainless Steel fittings are the best corrosion protection. Use in very harsh environments to protect against galvanic and chemical corrosion.

I  
P  
R  
A  
T  
I  
N  
G