

Defense

ANACONDA SEALTITE® CONDUIT

Flexible, armored protection,
ANAMET Electrical conduit and
fittings protect wiring and cable
from

- Intrusion and data breach
- Contamination
- Temperature extremes
- Stress and strain
- Corrosion

**TO
CONNECT
AND
PROTECT**

ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM
PHONE: (800) 230-3718

ANAMET Electrical, Inc. 
ANACONDA SEALTITE®

ANAMET Electrical is the exclusive manufacturer of
ANACONDA SEALTITE® liquid tight wiring conduit and
industrial stripwound hose.

Deliver security

ANACONDA SEALTITE®
conduit and fittings

ZHUA 3/8 to 4 inch diameter
Zero Halogen, Low smoke, UL Listed

SPECIFICATIONS

- Galvanized steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- UL Approved to UL-94 V-0 and UL-360. # E18917
- Meets or exceeds: ASTM-E162 (Flame spread); ASTM-E662 (Smoke density); Bombardier SMP-800C (Toxic gas generation)
- CSA File No. LL15275

APPLICATIONS

- Safety applications where low smoke and zero halogen are required

SHIELDTITE® Z1 3/8 to 4 inch diameter

EMI/EMP resistant. Zero Halogen, Low smoke

SPECIFICATIONS

- Bronze core with liquid tight TPU jacket
- Color: Gray
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- Special bronze core provides high-level shielding protection
- Meets MIL-STD-1310H
- Provides shielding effectiveness of 81 dB-119 dB at 1 kHz to 1 GHz

APPLICATIONS

- Applications where high shielding is required
- Power generation and communications

HFSS 3/8 to 2 inch diameter
Zero Halogen, Low smoke, Low flame

SPECIFICATIONS

- 316 stainless steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Safety applications where low smoke and zero halogen are required
- Rail and infrastructure applications

HCSS 3/8 to 2 inch diameter
Hot and Cold temperature

316 stainless steel

SPECIFICATIONS

- 316 stainless steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) and corrosion resistant

APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Superior wiring protection for petrochemical and offshore industries

SL-CAP 1/8 to 5/8 inch diameter

Square lock 304 stainless steel capillary armor

SPECIFICATIONS

- Type 304 stainless steel square lock (SL)
- Temperature: +450°F (+232°C) max.

APPLICATIONS

- Applications where corrosion is an issue and where no approvals are required
- Sensor cable protection
- OEM probe cables
- Optical fiber
- Instrumentation
- Temperature measuring devices
- Available in custom cut lengths

UI-CAP 5/32 to 1/2 inch diameter

Fully-interlocked 304 stainless steel capillary armor

SPECIFICATIONS

- Type 304 stainless steel fully-interlocked (UI-Cap)
- Temperature: +450°F (+232°C) max.

APPLICATIONS

- Applications where corrosion is an issue and where no approvals are required
- Sensor cable protection
- OEM probe cables
- Optical fiber
- Instrumentation
- Temperature measuring devices
- Available in custom cut lengths