


Electric Vehicle Charging



ANACONDA SEALTITE®

ANAMET Electrical conduit and fittings protect wiring from

- UV exposure
- Corrosion
- Water
- Strain and Wear

**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM

ANAMET Electrical, Inc. 

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

Protect from exposure and wear

ANACONDA SEALTITE® liquid tight conduit and fittings

UA ³/₈ to 4 inches diameter

UL and CSA approved, Liquid Tight, Flexible, Metallic, Electrical Conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Temperature range: -40°F to +176°F (-40°C to + 80°C)
- UL Approved to UL-360. DXHR.E18917
- CSA File No. LL15275

APPLICATIONS

- Applications where UL and CSA approvals are required

HTUA - HEAVY DUTY

³/₈ to 4 inches diameter

UL and CSA approved, High Temperature Flexible Conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Temperature range: -51°F to +221°F (-46°C to +105°C)
CSA max +167°F (+75°C)
- UL Approved #E18917, CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

APPLICATIONS

- Applications where UL and CSA approvals are required

STAINLESS STEEL AISI-316 FITTINGS

3/8 to 2 inches

SPECIFICATIONS

- AISI-316 body with AISI-304 Ferrule, a lock nut and PA6 clamping ring
- Each fitting has a sealing ring and locknut
- Color: Metallic
- Temp. range: -49°F to +221°F (-45°C to +105°C)
- cULus 514B Approved DWTT.E234207

APPLICATIONS

- Fitting for metallic flexible conduit
- Premium Stainless 316 for the best corrosion resistance.
- Compact design for tight spaces
- Available in 90-degree, 45-degree and straight configurations



Flexibly connect and protect wiring from UV exposure, corrosion and wear with ANACONDA SEALTITE® conduit and fittings.



RoHS WEEE Compliant

1-800-230-3718 cs@anametelectrical.com www.anametelectrical.com

ANAMET Electrical, Inc. 