


OEM Machine Building

ANACONDA SEALTITE® CONDUIT

Flexible, armored ANAMET Electrical conduit and fittings protect wiring and cable from

- Intrusion and data breach
- Contamination
- Temperature extremes
- Stress and strain
- Corrosion



**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM

ANAMET Electrical, Inc. 
ANACONDA SEALTITE®

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

Deliver security

ANACONDA SEALTITE® liquid tight conduit and fittings

- Suitable for hazardous locations
- Robots and sensors
- Extreme temperatures
- UL listing
- Corrosion resistant
- Zero Halogen
- EMI / EMP Shielding

Type Size

ZHUA 3/8 to 4 inch diameter

SHIELDTITE® Z1 3/8 to 4 inch diameter

MTC 3/8 to 2 inch diameter

HFSS 3/8 to 2 inch diameter

SL-CAP 1/8 to 5/8 inch diameter

UI-CAP 5/32 to 1/2 inch diameter



Black TPU Jackets on type HFSS and ZHUA conduit provide flexible, liquid tight, Halogen Free protection for wiring and cables.



RoHS WEEE Compliant

1-800-230-3718 cs@anametelectrical.com www.anametelectrical.com

ANAMET Electrical, Inc. 
ANACONDA SEALTITE®

ZHUA

3/8 to 4 inch diameter
Zero Halogen/low smoke, UL approved

SPECIFICATIONS

- Galvanized steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant
- UL Approved to UL-94 V-0 and UL-360. # E18917
- Meets or exceeds: ASTM-E162 (Flame spread); ASTM-E662 (Smoke density); Bombardier SMP-800C (Toxic gas generation)
- CSA File No. LL15275

APPLICATIONS

- Safety applications where low smoke and zero halogen are required

SHIELDTITE® Z1

3/8 to 4 inch diameter
EMI/EMP resistant Zero Halogen/low smoke

SPECIFICATIONS

- Bronze core with liquid tight TPU jacket
- Color: Gray
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant
- Special bronze core provides high-level shielding protection
- Meets MIL-STD-1310H
- Provides shielding effectiveness of 81 dB to 119 dB at 1 kHz to 1 GHz

APPLICATIONS

- Applications where high shielding is required
- Power generation and communications

MTC

1/2 to 1 inch diameter
Machine Tool Extra Flexible Conduit

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -4°F to +140°F (-20°C to +60°C)
- UV (sunlight) resistant
- Corrosion resistant
- Tight bend radius

APPLICATIONS

- High flexibility
- Machine tool industry



ANACONDA SEALTITE® conduit is rated for hazardous locations.



Use extreme temperature conduit to secure critical circuits.



A galvanized steel core jacketed with PVC gives MTC high flexibility.

HFSS

3/8 to 2 inch diameter
Zero Halogen/low smoke 316 stainless steel

SPECIFICATIONS

- 316 stainless steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Safety applications where low smoke and zero halogen are required

SL-CAP

1/8 to 5/8 inch diameter
Square lock 304 stainless steel
capillary armor

SPECIFICATIONS

- Type 304 stainless steel square lock (SL)
- Temperature: +450°F (+232°C) max.

APPLICATIONS

- Applications where corrosion is an issue and where no approvals are required
- Sensor cable protection
- OEM probe cables
- Optical fiber
- Instrumentation
- Temperature measuring devices
- Available in custom cut lengths

UI-CAP

5/32 to 1/2 inch diameter
Fully-interlocked 304 stainless steel
capillary armor

SPECIFICATIONS

- Type 304 stainless steel fully-interlocked (UI-Cap)
- Temperature: +450°F (+232°C) max.

APPLICATIONS

- Applications where corrosion is an issue and where no approvals are required
- Sensor cable protection
- OEM probe cables
- Optical fiber
- Instrumentation
- Temperature measuring devices
- Available in custom cut lengths

To find your nearest distributor for
ANACONDA SEALTITE® conduit and fittings, see
www.anacondasealtite.com/sales-rep-locator/

