

# Oil and Gas


## ANACONDA SEALTITE® CONDUIT

Flexible, oil resistant electrical conduit protects wiring from

- Intrusion
- Contamination
- Temperature extremes
- Stress and strain
- Corrosion

**TO  
CONNECT  
AND  
PROTECT**

PHONE: (800) 230-3718  
ANAMETELECTRICAL.COM  
SALES@ANAMETELECTRICAL.COM

**ANAMET Electrical, Inc.** 

ANAMET Electrical, Inc. is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

# ANACONDA SEALTITE® flexible conduit options

## OR 3/8 to 2 inch diameter

Oil resistant

### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -9°F to +221°F (-23°C to +105°C)
- UV (sunlight) and corrosion resistant
- Extra oil resistant

### APPLICATIONS

- Extreme resistance to oil
- Petrochemical and steel industries
- Applications where no approvals are required

## HTUA 3/8 to 4 inch diameter

Heavy Duty, High Temperature

UL Listed and CSA Approved



### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to + 221°F (-46°C to +105°C)  
CSA max +167°F (+75°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

### APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are required

## ZHUA 3/8 to 4 inches

Zero Halogen/low smoke, UL approved



### SPECIFICATIONS

- Galvanized steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- UL Approved to UL-94 V-0 and UL-360. # E18917
- Meets or exceeds: ASTM-E162 (Flame spread);  
ASTM-E662 (Smoke density); Bombardier  
SMP-800C (Toxic gas generation)
- CSA File No. LL15275

### APPLICATIONS

- Safety applications where low smoke and zero halogen are required



RoHS WEEE Compliant

## SS-HTUA



3/8 to 2 inch diameter

Extreme Temperature, Corrosion resistant,  
Stainless Steel Core

### SPECIFICATIONS

- Stainless Steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) and extra corrosion resistant
- Oil resistant

### APPLICATIONS

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where UL approval is required

## SS-ZHUA



3/8 to 2 inches Zero Halogen/low smoke 316  
stainless steel

### SPECIFICATIONS

- 316 stainless steel core with liquid tight TPE jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

### APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Safety applications where low smoke and zero halogen are required
- Applications where UL approval is required

## ATEX

Fittings 1/2 to 1 inch

Stainless Steel AISI-316 NPT/Metric

NOTE: ATEX fittings are not UL listed.

### SPECIFICATIONS

- AISI-316 Stainless Steel with PTFE clamping ring.
- Separate 2 compound epoxy is provided for creating a barrier.
- Color: Metallic
- Temp. range: -76°F to +266°F (-60°C to +130°C)
- IECEx-ATEX certified:  
CE0080 I M2 / II 2 GD / Ex d II C / Ex e II/ Ex d I / Ex tD A  
21 IP 66

### APPLICATIONS

- Metallic and Type B non-metallic flexible conduit
- Explosion-proof areas where Zone system used
- Machinery for export to other countries where Zone system used
- Superior corrosion resistance with 316 Stainless Steel

See: [www.iecex.com](http://www.iecex.com)