

# Outdoor Building and Construction

## ANACONDA SEALTITE®


ANAMET Electrical conduit and fittings protect wiring and cable from

- Intrusion and security breach
- Stress and strain
- Extreme temperatures
- Direct Burial
- Corrosion



**TO  
CONNECT  
AND  
PROTECT**

PHONE: (800) 230-3718  
ANAMETELECTRICAL.COM  
SALES@ANAMETELECTRICAL.COM

**ANAMET Electrical, Inc.**   
ANACONDA SEALTITE®

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

# Protect critical circuits

## ANACONDA SEALTITE® liquid tight conduit and fittings

### UA 3/8 to 4 inch diameter

UL Approved, Liquid Tight, Flexible, Metallic Electrical Conduit

#### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray, Black and custom colors
- Temp. range: -40°F to +176°F (-40°C to + 80°C)
- UV (sunlight) resistant
- Corrosion resistant
- UL Approved to UL-360. # E18917
- CSA File No. LL15275

#### APPLICATIONS

- Applications where UL and CSA approvals are required

### NMUA 3/8 to 2 inch diameter

Type B Non-Metallic Flexible Conduit

#### SPECIFICATIONS

- Co-extruded PVC conduit
- Temp. range: -17°F to +176°F (-27°C to +80°C)
- UV (sunlight) resistant
- Oil resistant
- UL Approved #E211327
- CSA Approved #20817

#### APPLICATIONS

- HVAC industry
- Commercial and industrial applications requiring UL & CSA approvals

### CNP 3/8 to 2 inch diameter

Type A Non-metallic Flexible Conduit

#### SPECIFICATIONS

- Smooth inner PVC core with outer oil resistant PVC cover bonded together with nylon reinforcing braid
- Temperature range: -4°F to +140°F (-20°C to 60°C)
- Color: Orange or Gray
- UV (sunlight) resistant, Flame retardant
- Oil resistant
- UL Approved #E75863
- CSA Approved #LL15275-10

#### APPLICATIONS

- Automation applications requiring continuous flexing
- Machine applications where non-metallic and flexing required

### CW-BLUE 3/8 to 2 inch diameter

Computer Flexible Conduit

#### SPECIFICATIONS

- Uses standard liquid-tight connectors for easy installation
- Galvanized steel core with liquid tight PVC jacket
- Color: Blue
- Temp. range: -40°F to + 176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant
- Protection of 1000 volt and lower potential circuits
- Approved as an equipment grounding conductor in sizes 3/8" through 1-1/4" if the total grounding path is 6 ft. or less, and the circuit conductors are protected by over-current devices rated at 20 amps or less for 3/8" and 1/2" and 60 amps or less for 3/4" through 1-1/4"
- Complies with UL standard 360 File No. E18917; CSA C22.2 File No. LL15275; and NEC article 350

#### APPLICATIONS

- Protect cables on information technology equipment in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"

### HTUA - HEAVY DUTY

3/8 to 4 inch diameter

UL/CSA High Temperature Flexible Conduit

#### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to + 221°F (-46°C to +105°C) CSA max +167°F (+75°C)
- UV (sunlight) resistant
- Corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

#### APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are required
- Steel and petrochemicals industries


### Stainless Steel Fittings

ANACONDA SEALTITE® fittings and conduit join securely to protect equipment from contamination, intrusion, strain, extreme temperatures and corrosion.



RoHS WEEE Compliant

1-800-230-3718 cs@anametelectrical.com www.anametelectrical.com

ANAMET Electrical, Inc.   
ANACONDA SEALTITE®