

Power and Energy


ANACONDA SEALTITE® CONDUIT

Identify critical circuits using bright, color conduit. ANAMET Electrical conduit and fittings protect wiring and cable from

- Intrusion and security breach
- Stress and strain
- Extreme temperatures
- Water and corrosion

**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETELECTRICAL.COM
SALES@ANAMETELECTRICAL.COM

ANAMET Electrical, Inc. 
ANACONDA SEALTITE®

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

Protect energy generation and distribution systems

- Enclosures
- Switchgear
- Power distribution
- Data cables
- Instrumentation
- Relays
- Sensors



Largest Available Conduit Fittings Diameter

NWC	4-inches
HTUA	4-inches
UA	4-inches
HXC	2-inches



RoHS WEEE Compliant (RoHS except for NWC in 2021)

ANACONDA SEALTITE® flexible conduit options

NWC 3/8 to 4 inch diameter

Radiation resistant

SPECIFICATIONS

- Galvanized steel core with liquid tight polyethylene jacket
- Color: Black
- Temp. range: -40°F to + 192°F (-40°C to +89°C)
- Suitable for use in nuclear containment areas
- Uses standard liquid-tight connectors for easy installation

APPLICATIONS

- Applications requiring radiation resistance
- Power generation, military and medical

HTUA 3/8 to 4 inch diameter

Heavy Duty, High Temperature

UL Listed and CSA Approved

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to + 221°F (-46°C to +105°C)
CSA max +167°F (+75°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are required

HXC 3/8 to 2 inch diameter

Extreme Temperature, Zero Halogen

SPECIFICATIONS

- Galvanized steel core with liquid tight TPE jacket
- Color: Black
- Temp. range: Static installations -76°F to +302°F (-60°C to +150°C). Dynamic installations at atmospheric pressure rated for -76°F to +221°F (-60°C to +105°C)
- UV (sunlight) and extra corrosion resistant
- Oil resistant

APPLICATIONS

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required

UA 3/8 to 4 inch diameter

UL Listed and CSA Approved

SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray, Black and custom colors
- Temp. range: -40°F to +176°F (-40°C to + 80°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275

APPLICATIONS:

- Applications where UL and CSA approvals are required