


UA COLOR UL LISTED AND CSA APPROVED CONDUIT

LFMC SEALTITE® UA
UL AND CSA APPROVED FLEXIBLE CONDUIT



Square-Locked Design with integral bonding wire 3/8" - 1-1/4"

SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray, Black and custom colors
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant, Corrosion resistant
- Complies with UL 360 #E18917, CSA C22.2 #LL15275 and NEC Article 350

APPLICATIONS:

- Applications where UL and CSA approvals are required



Trade Size (mm)	Color	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)
				Min	Max	Min	Max		
1/2" (16)	Brown	434009-0103	100	0.622	0.642	0.822	0.840	3.5	29
	Brown	434009-0101	500						
	Brown	434009-0102	1000						
	Pink	434009-0107	500						
	Pink	434009-0108	1000						
	Purple	434009-0140	500						
	Purple	434009-0139	1000						
	Yellow	434009-0167	500						
	Yellow	434009-0168	1000						
	Orange	434009-0179	100						
	Orange	434009-0181	100						
	Red	434009-0185	100						
	Red	434009-0189	500						
	Red	434009-0188	1000						
	Green	434009-0187	500						
	Green	434009-0186	1000						
White	34412	100							
White	34414	500							
White	34413	1000							
3/4" (21)	Brown	434019-0102	500	0.820	0.840	1.030	1.050	5.0	44
	Purple	434019-0139	500						
	Purple	434019-0140	1000						
	Yellow	434019-0156	100						
	Yellow	434019-0158	500						
	Yellow	434019-0159	1000						
	Orange	434019-0181	500						
	Orange	434019-0182	1000						
	Red	434019-0187	100						
	Red	434019-0188	500						
	Red	434019-0189	1000						
	Green	434019-0184	100						
	Green	434019-0185	500						
	Green	434019-0186	1000						
	White	34422	100						
	White	34428	500						
White	34429	1000							

METALLIC SEALTITE®

U
A

C
O
L
O
R
S

FITTINGS FINDER



IP 66/67 with approved fittings